

## STRUCTURAL NOTES

Ⓐ	MAIN POSTS	168mm (6- ") OD GALVANIZED STEEL PIPE
Ⓑ	MAIN POSTS	114mm (4- ") OD GALVANIZED STEEL PIPE
Ⓒ	MAIN POSTS	90mm (3- ") OD GALVANIZED STEEL PIPE
Ⓓ	RAILS	64mm (2- ") OD GALVANIZED STEEL PIPE
Ⓔ	RAILS	48mm (2") OD GALVANIZED STEEL PIPE
Ⓕ	END CAPS	ALL END CAPS MUST BE WELDED IN PLACE
Ⓖ	MESH	CHAIN LINK FABRIC FOR BACKSTOP, WINGS AND PLAYERS ENCLOSURE TO BE 50mm (2") MESH OF GALVANIZED STEEL, 6 GAUGE WIRE, EDGES KNUCKLED UNDER

## GENERAL NOTES

- 1) ALL POSTS, RAILS, CAPS, ELBOWS AND OTHER JOINTS MUST BE WELDED.
- 2) TOP RAIL OF OVERHANG MUST BE CONTINUOUS PIPE.
- 3) CHAIN LINK FABRIC TO BE ATTACHED TO INSIDE OF BACKSTOP SCREEN AND THE TOP OF OVERHANG.
- 4) FABRIC OF OVERHANG TO EXTEND 25mm BEYOND PIPE FRAME.
- 5) TENSION BANDS TO BE 400mm O/C. BOLT ENDS TO BE AT BACK OF BACKSTOP SCREEN.
- 6) 9 GAUGE WIRE TIES TO BE 300mm O/C WRAPPED TWICE THROUGH MESH.
- 7) ALL STEEL PIPE TO BE SCHEDULE 40 GALVANIZED.
- 8) CONSULT WITH STRUCTURAL AND GEOTECHNICAL ENGINEER FOR ALL FOOTING REQUIREMENTS



OPERATIONS SECTION

## BASEBALL - BACKSTOP FENCE NOTES AND SCHEDULES (4 OF 4)

DWG. No.

**AS-606**

DATE

SEPT. 2020

REVISION No.