


## STRUCTURAL NOTES

- |     |                  |   |
|-----|------------------|---|
| (A) | MAIN POSTS       | 168mm (6-1/2") OD GALVANIZED STEEL PIPE   |
| (B) | MAIN POSTS       | 114mm (4-1/2") OD GALVANIZED STEEL PIPE   |
| (C) | MAIN POSTS       | 90mm (3-1/2") OD GALVANIZED STEEL PIPE  |
| (D) | RAILS            | 64mm (2-1/2") OD GALVANIZED STEEL PIPE  |
| (E) | RAILS            | 48mm (2") OD GALVANIZED STEEL PIPE  |
| (F) | END CAPS         | ALL END CAPS MUST BE WELDED IN PLACE  |
| (G) | MESH<br>OVERHANG | CHAIN LINK FABRIC FOR BACKSTOP, WINGS AND<br>PLAYERS ENCLOSURE TO BE 50mm (2") MESH OF<br>GALVANIZED STEEL, 6 GAUGE WIRE, EDGES KNUCKLED<br>UNDER |

## GENERAL NOTES

- 1) ALL POSTS, RAILS, CAPS, ELBOWS AND OTHER JOINTS MUST BE WELDED.
- 2) TOP RAIL OF OVERHANG MUST BE CONTINUOUS PIPE.
- 3) CHAIN LINK FABRIC TO BE ATTACHED TO INSIDE OF BACKSTOP SCREEN AND THE TOP OF OVERHANG.
- 4) FABRIC OF OVERHANG TO EXTEND 25mm BEYOND PIPE FRAME.
- 5) TENSION BANDS TO BE 400mm O/C. BOLT ENDS TO BE AT BACK OF BACKSTOP SCREEN.
- 6) 9 GAUGE WIRE TIES TO BE 300mm O/C WRAPPED TWICE THROUGH MESH.
- 7) ALL STEEL PIPE TO BE SCHEDULE 40 GALVANIZED.



OPERATIONS SECTION

## SOFTBALL - SENIOR FIELD BACKSTOP FENCE - NOTES & SCHEDULES (4 OF 4)

DWG. No.

**AS-618**

DATE

SEPT. 2020

REVISION No.